



FEATURES:

- Available from ½" to 4" diameters
- Manufactured from flexible HDPE, makes gradual bends without special equipment
- Continuous lengths reduce joining costs
- Excellent low temperature properties, allows installation in cold climates
- Outstanding long term cable protection from shifting ground, rock and root impingement
- Provides a permanent pathway, simplifies future cable repairs or replacement
- SDR 11 & SDR 13.5
- Pre-installed 1,250 lbs Pull Tape

DIVIDED REEL PACKAGING:

Dura-Line's Smoothwall conduit can be provided on "divided reels".

Up to three conduits can be wrapped simultaneously on the same reel, providing a "divided reel". If multiple conduits need to be placed at one time, it's the easiest way to handle a single reel onsite. Up to three conduits can be placed from one reel versus multiple reels with individual conduits. All conduits must be pulled off the reel at the same time.



Divided Reels with 3 conduits on one reel.

Dura-Line Part #	Description	Segments	Packaging*	Standard Reel Size
10013296	1.25" Smoothwall SDR 13.5	Segment 1: Orange	7,200' reel total	96x45
	3-way Divided Reel with 1250# Pull Tape	Segment 2: Orange	2,400'/segment	
		Segment 3: Orange		

*Total footage on reel of 1.25" Smoothwall conduit with 3 segments is 7,200' – each "segment" length is 2,400'
To calculate segment length, divide total footage by number of segments.

SMOOTHWALL w PULL TAPE

TL9000



Wall Type	Pipe Size	1/2"	3/4"	1"	1 1/4"	1 1/2"	2"	3"	4"
	Nom OD (in)	0.840	1.050	1.315	1.660	1.900	2.375	3.500	4.500
	OD Tolerance +/-	0.004	0.005	0.007	0.008	0.010	0.012	0.018	0.023
	Bend Radius (in) – Supported	8	10	13	17	19	24	39	50
	Bend Radius (in) – Unsupported	16	20	26	34	38	48	78	100

SDR-11	Min. Wall (in)	0.076	0.095	0.119	0.151	0.173	0.216	0.318	0.409
	Wall Tolerance +	0.020	0.020	0.020	0.020	0.021	0.026	0.038	0.049
	Avg ID (in)	0.668	0.840	1.057	1.338	1.533	1.917	2.826	3.633
	Weight (#/ft)	0.079	0.124	0.195	0.312	0.409	0.638	1.385	2.291
	Safe Working Load	440	687	1,078	1,717	2,249	3,515	7,633	12,618
	Standard Packaging (SPQ) feet			10,000	8,000	6,000	4,000	1,000	750
	Minimum Order Quantity (MOQ) feet			10,000	10,000	10,000	10,000	1,000	750
	Dura-Line Part #								
	Conduit Color – Orange			10010050	10003070	10010051	10000738	10010052	10010053

Wall Type	Pipe Size	1/2"	3/4"	1"	1 1/4"	1 1/2"	2"	3"	4"
	Nom OD (in)	0.840	1.050	1.315	1.660	1.900	2.375	3.500	4.500
	OD Tolerance +/-	0.004	0.005	0.007	0.008	0.010	0.012	0.018	0.023
	Bend Radius (in) – Supported	8	10	13	17	19	24	39	50
	Bend Radius (in) – Unsupported	16	20	26	34	38	48	78	100

SDR-13.5	Min. Wall (in)	0.062	0.078	0.097	0.123	0.141	0.176	0.259	0.333
	Wall Tolerance +	0.020	0.020	0.020	0.020	0.020	0.021	0.031	0.040
	Avg ID (in)	0.696	0.874	1.101	1.394	1.598	2.002	2.951	3.794
	Weight (#/ft)	0.066	0.104	0.162	0.259	0.340	0.530	1.151	1.902
	Safe Working Load	365	570	894	1,425	1,867	2,917	6,335	10,472
	Standard Packaging (SPQ) feet	2,500	10,000	10,000	8,000	6,000	4,000	1,000	750
	Minimum Order Quantity (MOQ) feet	10,000	10,000	5,000	10,000	10,000	2,500	1,000	750
	Dura-Line Part #								
	Conduit – Orange	10009962	10003003	10004437	10005562	10003094	10000766	10000804	10007957
	Conduit – Orange DIVIDED REEL				10013296		10009810		
	Conduit – Blue						10009811		
	Conduit – Green						10010935		
	Conduit – Brown		10013025		10013020				
	Conduit – Orange / Stripe – Red		10013026		10013021				
	Conduit – Orange / Stripe – Lilac		10013027		10013022				
	Conduit – Orange / Stripe – Black		10013028		10013023				
	Conduit – Orange / Stripe – White		10013032						
	Conduit – Orange / Stripe – Blue		10013033						
	Conduit – Orange / Stripe – Green		10013034						
	Conduit – Orange / Stripe – Brown		10013035						
	Conduit – Orange / Stripe – Gray		10013036						
	Conduit – Orange / Stripe – Yellow		10013037						
	Conduit – Orange / Stripe – Terra Cotta								